(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 29 January 2004 (29.01.2004)

PCT

(10) International Publication Number WO 2004/010666 A1

(51) International Patent Classification⁷:

(21) International Application Number:

PCT/IB2003/003028

H04L 25/06

(22) International Filing Date:

8 July 2003 (08.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0216703.9

18 July 2002 (18.07.2002) GB

- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PAYNE, Adrian, W. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB). CALD-WELL, Richard, J. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).


- (74) Agent: WILLIAMSON, Paul, L.; Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FSK RECEIVER HAVING A VARIABLE THRESHOLD SLICER STAGE AND CORRESPONDING METHOD



(57) Abstract: A receiver having a variable threshold slicer stage, comprises a demodulator (14) for providing asynchronously samples of over-sampled raw demodulated data, a shift register (60) for delaying the over-sampled data by up to 2 bit periods. Samples in stages (62, 72) corresponding to substantially the mid-points in two successive bit periods are combined to form a signal (fX_n) to be applied to a bit slicer (22). A bit stream signal from the bit slicer (22) is delayed by two concatenated shift registers (30,32) for 2 bit periods and is contemporaneously applied to a clock recovery circuit (74) for producing clock signals at the data rate for sampling the delayed sliced signal (Bn-2) at the center of bit to produce an output signal (34).

